

COMPACT OFFICE IP PHONE

ES206



EP+APP



Multi angle
bracket



RJ9 headset



HD Voice




ECS



Programmable
keys

- 2 lines, 13 programmable keys.
- Demountable bracket to provide multi-angle.
- Multi-language, e.g: Chinese, English, French, Russian, Italian and etc.
- 2*10/100M Ethernet ports, support POE.
- Auto-provision, HTTP/TFTP/FTP, TR069, PNP.



36°



50°

Technical Datasheet

Phone Features

- 2 SIP accounts, Hot line
- Call hold, Call waiting, Call forward, Call return; Call transfer (blind/busy/ask) Caller ID display, Redial, Mute, DND
- Auto-answer, 3-way conferencing
- Speed dial, SMS, Voicemail
- Tone scheme, Volume control
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Black list, Hand-free indicator.
- Call history: dialed/received/missed (50-entries);
- Soft keys programmable, Supports PC control
- Multi-Language: Chinese, English, French, Russian, Italian, Polish, Spanish, Portuguesa, Portuguesa-Brasil, Turkish

Advanced Features

- 13 programmable keys
- XML Phone Book search and input & output
- Enterprise phone book(800 entries)
- LDAP phone book

IP PBX System Integration

- Busy lamp field (BLF), BLF list
- Bridged line appearance (BLA)
- DND & Forward synchronization
- Intercom, Paging, Music on hold
- Call pickup, Dial Plan, Call recording
- Anonymous call, Anonymous call rejection
- Network conference, Distinctive ring tone

Codes and Voice Features

- Wideband Codec: G.722
- Narrowband codec: G.711 μ A, G.723.1 G.726, G.729AB, iLBC
- VAD, CNG, AEC, AGC
- Full-duplex

Security

- LLDP, VPN(L2TP) ,802.1x
- Transport Layer Security (TLS)
- Digest authentication using MD5/MD5-session
- Secure configuration file via AES encryption
- Phone lock for personal privacy protection
- Admin/User 2-level configuration mode

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- DNS SRV (RFC3263); IPv6
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP/HTTPS Web Management
- IP Assignment: Static/DHCP/PPPoE
- Bridge/Router mode for PC port
- TFTP/DHCP/PPPoE client
- DNS client, NAT/DHCP server

Management

- Auto-provision via FTP/TFTP/HTTP/HTTPS; PNP;SNMP V1/2,TR069 optional
- Configuration: browser/phone/auto-provision
- Trace package and system log export

Physical Features

- 128*64 graphic LCD, Backlight
- 33 keys, including 13 programmable keys,
- 3 LEDs: 2* account lights, 1*status light
- 1* RJ-9 handset port
- 1*RJ-9 headset port(Optional)
- 1*PSTN port(Optional)
- 2xRJ45 10/100M Ethernet ports
- Power adapter: AC 100~240V input and DC 5V/1A output
- Power over Ethernet ,IEEE 802.3af,class 0(Optional)
- Power consumption: 1.5W
- Net weight: 0.62kg
- Dimension: 213*157*39mm
- Operating humidity: 10~95%
- Storage temperature: up to 60°C

Package Features


- Qty/CTN: 10 PCS
- N.W/CTN: 6.2kg
- G.W/CTN: 8.5kg
- Carton Meas: 430x345x250mm

Certifications

FC CE RoHS



COMPATIBLE WITH THE PLATFORM



ESCENE COMMUNICATION CO.,LTD

Add: Floor 4 building C YueAn Industrial Park No.51 huangcun Road Tianhe District, Guangzhou, China.

Tel: (86) 20-82320720

E-mail: sales@escene.cn

www.escene.cn/en